

# Rear View Monitor For Vehicle



## Features

- High Resolution 7 "TFT LCD panel
- Free Input Voltage (DC 10V ~ DC 32V)
- NTSC / PAL Compatibility
- 4 Camera Inputs / 1 AV Input / 1AV Out
- Multiple Display Mode (Single, Split, Triple, Quad)
- Automatic Picture Display (5 Triggering functions)
- Auto Scanning function
- Automatic Brightness Sensor (DAY/NIGHT)
- Built-in Speaker
- OSD with  $\mu$ -com



**ECL-70M**



**ECL-70CQ**

## Specifications

*Specifications are subject to change without notice.*

Model No.	ECL-70M
Power Input	DC 12V From ECL-70 CQ
Power Cons.	Max 10 Watt.
Video System	NTSC/PAL standard signal
Resolution	336,960 Pixels (1,440 (w) X 234 (h))mm
Screen Size	7.0 inch (Digonal)
Auto Con./Bright.	Day & Night Sensor
Operating Temp.	-25°C ~ 75°C
Ambient Condition	Indoor Use Only
Vibration	4 G
Dimension	197 (W)X 138(H)X 32.2(D)mm (7.75(W) X5.43(H)X 1.3(D)inch)
Weight	Approx. 1.0 Kg

Model No.	ECL-70CQ
Power Input	DC 10V ~ 32V ( Car Battery)
Power Cons.	Max 24 Watt.
Video System	NTSC/ PAL standard signal
Sync. System	Internal
CA Input (4 CH)	Mini DIN 4p , 1Vp-p, 75 $\Omega$ (Normal, Tilt, Shutter camera compatible)
A/V Output(1 CH)	RCA, Composite Video Signal, 75 $\Omega$ , 1Vp-p,
A/V Input(1 CH)	RCA, Composite Video Signal, 75 $\Omega$ , 1Vp-p.
Operating Temp.	-25°C ~ 75°C ( -13°F ~ 167°F)
Vibration	4G
Dimension	154(W)X 28 (H)X 105 (D)mm (6.06 (W)X1.1 (H)X.4.13 (D)Inch)